

CAR-REP[®]
automotive products



PROFESSIONAL SMART REPAIR



2K



TWO COMPONENTS – ONE COMPARTMENT

UNLIMITED POTLIFE

THE FUTURE OF 2K PAINTING



ONE COMPARTMENT CAN



ALWAYS READY TO USE




UNLIMITED POTLIFE



ORIGINAL 2K QUALITY

How does it work?



● PROPELLANT

● 2K RESIN

● DE-ACTIVATED HARDENER

● 2K REACTION



Easy to use

1. Shake

2. Spray

3. Clean

4. Use again



WISE 2K™ technology licensed by Wisespray International Ltd. www.wisespray.com. International patents pending. Two component spray paint. One compartment can. Unlimited Potlife. WISE 2K™ is a trademark or registered trademark of Wisespray International Ltd.

2K SMART REPAIR

2K AEROSOL SPRAY VS SPRAY GUN



NO PREMIXING



NO PAINT LOSSES



NO PAINT GUN



NO CLEANING



**UNLIMITED
POTLIFE**




**ORIGINAL 2K
REFINISH QUALITY**

50%

COST SAVINGS


CHOOSE SMART REPAIR

Nozzle options



NARROW TARGETS

LOW ROUND is perfect for small and thin targets, as spray pattern is small and round. Spray diameter is only 40 mm / 1 in. Paint ejection quantity of paint is 50 g / 1.5 oz / min. Painting distance 15-25 cm / 6-10 in. **Art. No. r85600**




SMALL SPOTS

LOW FAN has a wide fan spraying pattern. Spray diameter is 100 mm / 4 in, but it has a lower output of paint 60 g / 2 oz / min. The spray patterns' edge is soft. Painting distance 15-25 cm / 6-10 in. Fan can be set to vertical or horizontal positions. **Art. No. r85618**




BIG SPOTS

MEDIUM FAN is versatile. The spray pattern is a wide fan. Spray diameter is 80 mm / 3 oz. Output of paint is 90 g / 3 oz / min. Painting distance 15-25 cm / 6-10 in. Fan can be set to vertical or horizontal positions. **Art. No. r85625**



BIG PARTS

HIGH FAN is for a high output on large areas. Paint output is very high 120 g / 4 oz / min. and spray diameter is very large 120 mm / 5 in. Painting distance is 15-25 cm / 6-10 in. Fan can be set to vertical or horizontal positions. **Art. No. r85617**



CLEAR COAT

MEDIUM FAN is for a high output on large areas. Paint output is 100 g / 3.5 oz / min. and spray diameter is very large 140 mm / 5.5 in. Painting distance is 15-25 cm / 6-10 in. Fan can be set to vertical or horizontal positions. **Art. No. r85630**



ORIGINAL 2K QUALITY



**SCRATCH
RESISTANT**



**CHEMICAL
RESISTANT**



**ABRASION
RESISTANT**



**FLEXIBLE
SURFACE**



**CORROSION
RESISTANT**



BONDS ON ALMOST ANY SURFACE.

- | | | |
|-----------|------------------|----------------------|
| METAL | | |
| ALUMINIUM | GALVANIZED METAL | COPPER |
| CHROME | WOOD | STONE |
| CERAMICS | GLASS | MOST PLASTICS |



EPOXY PRIMER

CAR-REP® 2K EPOXY PRIMER with anti-corrosion pigments creates humidity and chemical resistance. It provides an adhesion bridge layer for putties, which can be applied directly on the primer without sanding. Suitable on all kind of metals (including galvanized metal, aluminium, copper, brass) as well as carbon fiber substrates and most plastics used in automotive OEM. Quick 20 minutes baking time with infrared speeds up the primer process and ensures excellent time and cost savings. Car-Rep® 2K Epoxy Primer can be applied outside spray booths, which is both convenient and efficient.

FEATURES

- 1 Fast application within a quick 20 minutes infrared baking time at 70 °C / 160 °F
- 2 Can be applied directly to various metals, plastics and carbon fiber
- 3 Putties can be applied directly to primed surfaces
- 4 Excellent anti-corrosion and bonding properties
- 5 Easy application with short flash off-times
- 6 No potlife. It can be used repeatedly again and again

C2123
Car-Rep® 2K Epoxy Primer Grey 400ml

C2130
Car-Rep® 2K Epoxy Primer Black 400ml




SCAN for more info
at car-rep.com

INSTRUCTIONS



DRY IN 20 °C / 68 °F



INFRARED



IMPORTANT INSTRUCTIONS VALID AT 20°C / 68°F, RELATIVE AIR HUMIDITY 35% - 75%. NOT RECOMMENDED TO USE <18°C / <65°F.

NOZZLE OPTIONS

MEDIUM FAN - Narrow spray - r85625



OTHER OPTIONS

LOW ROUND - Narrow spray - r85600



LOW FAN - Wide spray - r85618



HIGH FAN - Wide spray - r85617





PRIMER FILLER

CAR-REP® 2K PRIMER FILLER is designed to optimize working hours. The primer filler mix compound ensures excellent anti-corrosion properties, high filling power, easy application, fast drying time and good sandability. Available in several shades of grey to be adapted to the Base Coat colour. For maximum adhesion and corrosion resistance, Car-Rep® 2K Primer Fillers are recommended to be used together with Car-Rep® 2K Epoxy Primer. Car-Rep® 2K Primer Filler can be applied outside spray booths, which is time and cost-efficient.

FEATURES

1 High filling power with short 3 min flash-off time

2 After 15 minutes final flash-off the surface can be infrared dried or baked

3 Semi-gloss surface, defects easy to see, good sandability

4 Excellent anti-corrosion and bonding properties

5 Can be topcoated with solvent or waterborne basecoats

6 No potlife. It can be used repeatedly again and again

C2120
Car-Rep® 2K Primer Filler Epoxy Light Grey 400ml


C2121
Car-Rep® 2K Primer Filler Epoxy Dark Grey 400ml

C2122
Car-Rep® 2K Primer Filler Epoxy Mid Grey 400ml



SCAN for more info
at car-rep.com


INSTRUCTIONS



IMPORTANT INSTRUCTIONS VALID AT 20°C / 68°F, RELATIVE AIR HUMIDITY 35% - 75%. NOT RECOMMENDED TO USE <18°C / <65°F.

NOZZLE OPTIONS

MEDIUM FAN - Narrow spray - r85625




OTHER OPTIONS

LOW FAN - Wide spray - r85618



HIGH FAN - Wide spray - r85617





TOP COATS

CAR-REP® 2K TOP COATS make 2-component painting as easy and user-friendly as painting with any ordinary 1-component spray paint. When sprayed, the chemical hardening process takes immediately place in atmospheric pressure. This ensures that Car-Rep 2K has the same characteristics in terms of adhesion, corrosion, scratch and chemical resistance as traditional 2-component paints systems, where the paint and the hardener have to be pre-mixed. Car-Rep 2K bonds on almost any surface metal, aluminum, galvanized metal, copper, chrome, wood, stone, ceramics, glass and most plastics. It bonds also on previously painted 1-component or 2-component paint surfaces such as acrylics, PU, epoxy and powder coating.

FEATURES

- 1 Can be applied directly to various metals, plastics and carbon fiber
- 2 Excellent anti-corrosion and bonding properties
- 3 Easy application with short flash off-times
- 4 No potlife. It can be used repeatedly again and again

C231023
Car-Rep® 2K
Traffic Yellow
RAL1023 400ml

C232004
Car-Rep® 2K
Pure Orange
RAL2004 400ml

C233000
Car-Rep® 2K
Flame Red
RAL3000 400ml

C235010
Car-Rep® 2K
Gentian Blue
RAL5010 400ml

C236005
Car-Rep® 2K
British Racing Green
RAL6005 400ml

C237016
Car-Rep® 2K
Anthracite Grey
RAL7016 400ml

C239005M
Car-Rep® 2K
Jet Black Matte
RAL9005 400ml

C239005S
Car-Rep® 2K
Jet Black Satin
RAL9005 400ml

C239005
Car-Rep® 2K
Jet Black Gloss
RAL9005 400ml

C239010
Car-Rep® 2K
Pure White
RAL9010 400ml

SCAN for more info
at car-rep.com



PETROL RESISTANT	STRONG BOND	VERY HARD	3 MINUTES	2K PAINT	15-25 CM / 6-10 IN
3 LAYERS 3 MIN	CLEAN 5 SEC	20°C / 68°F 3-5 H	20°C / 68°F 12 H	CHEMICAL RESISTANCE 8-10 DAYS	

IMPORTANT INSTRUCTIONS VALID AT 20°C / 68°F, RELATIVE AIR HUMIDITY 35% - 75%. NOT RECOMMENDED TO USE <18°C / <65°F.

NOZZLE OPTIONS

MEDIUM FAN - Narrow spray - r85625




OTHER OPTIONS

LOW ROUND - Narrow spray - r85600



LOW FAN - Wide spray - r85618



HIGH FAN - Wide spray - r85617





PU CLEAR COAT

CAR-REP® 2K PU CLEAR COAT is crystal clear, very strong, extremely durable, and forms a chip and UV-resistant film. It is easy to apply and immediately forms a deep and shiny surface without the risk of dripping. It can be applied to solventborne and waterborne basecoats. The drying time can be boosted with shortwave infrared or baking.

FEATURES

- 1 Easy application with reduced sagging risk
- 2 Can be applied over solventborne and waterborne basecoats
- 3 Very fast drying properties 40 min infrared, 12 hr at 20 °C
- 4 Excellent durability, good hold-out and retention
- 5 Great polishability
- 6 No potlife. It can be used repeatedly again and again

C2202M
Car-Rep® 2K PU Clear Coat Matt 400ml


C2201S
Car-Rep® 2K PU Clear Coat Satin 400ml

C2200
Car-Rep® 2K PU Clear Coat High Gloss 400ml



SCAN for more info
at car-rep.com



INSTRUCTIONS



IMPORTANT INSTRUCTIONS VALID AT 20°C / 68°F, RELATIVE AIR HUMIDITY 35% - 75%. NOT RECOMMENDED TO USE <18°C / <65°F.

NOZZLE OPTION

MEDIUM FAN - Wide spray - r85630



100 g / 3.5 oz / min.

140 mm
/ 5.5 in

CAR-REP[®]
automotive products

MASTON

Maston / Car-Rep Europe
Teollisuustie 10, FI-02880 Veikkola, Finland • Tel. +358 20 7188 580
www.maston.fi • maston@maston.fi

Maston / Car-Rep North America
205 North Michigan Avenue, Suite 810, Chicago, Illinois, USA 60601
Tel: +1-702-718-1588 • Tollfree: 1-866-541-1694
www.car-rep.com • info@car-rep.com

ART NR:
CR200PROFenUS

